

TERIUM 3XP2



ÁREA DE TRABAJO DE 30 CM

UV DTF

IMPRESIÓN DURADERA Y RESISTENTE

Stickers con relieve y barniz ideales para cualquier superficie.

Printhead	EPSON i1600 / XP600		Print speed	size: A3	6 Pass: 4m ² /h, 8 Pass: 2.1m ² /h, 12 Pass: 1m ² /h
Number of print head	2		Printing accuracy	size: A1 / 600	6 Pass: 4.5m ² /h, 8 Pass: 3.1m ² /h, 12 Pass: 1.8m ² /h
Printer size (L*w*Hmm)	size: A3	960x680x1000	Environmental conditions	size: i1600 A1/780	6 Pass: 8m ² /h, 8 Pass: 5.8m ² /h, 12 Pass: 4m ² /h
	size: A1 / 600	1380x860x1000		360*2400dpi, 360*3600dpi, 720*2400dpi (6 Pss, 8Pass, 12Pass)	
	size: i1600 A1/780	1840x960x1300		Temperature: 20-28°C Relative Humidity: 65% - 75%	
Maximum printing width	300 / 600 mm		Ink type and configuration	UV ink C / M / Y / K / W - Varnish	
Weight (kg)	size: A3	140 KG	Working power supply	220V / 110 V 50HZ / 60 HZ	
	size: A1 / 600	168 KG	The ironing temperature	160 - 170°C cold / hot to tear	
	size: i1600 A1/780	190 KG		Printer: 350w Powder dryer: 3400W	
Outer packing size (L*w*Hmm)	size: A3	1060(L)*890(W)*800(H)	Power	(30 - 65) Pre - heater, printing bed heater, rear heater 30°C - 65°C	
	size: A1 / 600	1460(L)*890(W)*800(H)	Three heating sections		
	size: i1600 A1/780	1850(L)*980(W)*880(H)			
Printing software	Photoprint				
Language	Chinese / English				